

# form POS 960

## The top of the new line of Olivetti PC POS systems.

FORM POS 960 is the perfect combination of **design, technology and reliability**, designed to effectively respond to the most **complex needs of the Retail and Hospitality markets**.

The **design's elegance and ergonomics** characterize the **robust aluminum structure**.

The capacitive and multi touch 15" touch screen (TRUE FLAT) monitor, combined with the **latest Intel® processor**, guarantee **high levels of performance** even in environments that use the most advanced management applications.

The SSD (Solid State Drive) technology of the hard disk, which allows **high performance and low power consumption**, ensures the system further operational efficiency and reliability.



---

HIGH PERFORMANCE OFFERED BY THE INTEL® CORE™ I3 PROCESSOR, 2.7 GHZ

SSD-TYPE MASS STORAGE WITH 128 MB OF CAPACITY

TRUE FLAT IP65 FRONT MONITOR RESISTANT TO WATER AND DUST


FRONT MONITOR WITH TILTABLE ANGLE (0° -90°)

POSSIBILITY TO INTEGRATE A SECOND 10.1" DISPLAY, OR A 2X20 CUSTOMER DISPLAY, AN MSR OR AN MSR WITH I-BUTTON

---



Magnetic card reader with i-button optional



Display with tiltable angle (0° -90°)



Easy access to communication ports

## TECHNICAL SPECIFICATIONS

### MAIN BOARD

<b>CPU</b>	Skylake-S Intel® Core™ i3-6100TE processor (Dual-core, 4M Cache, 2.7 GHz, TDP 35 watt)
<b>Graphic</b>	Intel® HD Graphics
<b>System memory</b>	4GB, DDR4 SO-DIMM 1866/2133MHz x 1
<b>Compatible Operating Systems</b>	Windows 10 IoT Enterprise Value, Windows Embedded POSReady 7, Windows 7, Professional for Embedded Systems, Windows Embedded 8.1 Industry

### TOUCH DISPLAY

<b>Dimensions</b>	15.1" 4:3 TFT LCD
<b>Brightness</b>	250 nit
<b>Resolution</b>	1024 X 768 pixel
<b>Panel Backlight Type</b>	LED - 50K hours of life
<b>Front Panel Type</b>	Bazel-free
<b>Tilt Angle</b>	0°-90°
<b>Touch Screen</b>	P-cap Multi-touch - with 7H hardness over lens

### STORAGE

<b>Interfaces</b>	2 x SATA3 (6.0Gb/s)
<b>SSD/HDD</b>	128GB Slot mSATA x 1(per SSD) Optional: 320GB - 2.5"HDD x 1

### I/O PORTS

<b>Serials</b>	Serial ports x 6: DB-9 Pin9 con RI/5V/12V selectable by BIOS COM 1/2: RS-232, RJ-50 with convert to DB-9 COM 3/4: RS-232/422/485 selectable by BIOS, RJ-50 with convert to DB-9 COM 5: RS-232 reserved for customer display 2x20 VFD COM 6: RS-232, reserved
<b>USB</b>	3 x USB 2.0 1 x USB 3.0
<b>LAN</b>	1 x Gigabit RJ-45 Ethernet Wake on LAN supported
<b>Cash Drawer</b>	1 x RJ12 - supports 12V/24V DC
<b>Audio</b>	2 x Speakers 2W
<b>DP / HDMI</b>	1 x mini Display Port (supporting active converter cable to VGA, DVI, HDMI)
<b>DC-IN</b>	24VDC input x 1, 4pins jack
<b>DC-OUT</b>	12VDC x 1/1A output

### MISCELLANEOUS

<b>Color</b>	Black
<b>Material</b>	Aluminum
<b>Mounting mechanism</b>	Supports VESA Mount
<b>Safety and Marks</b>	CE / WEEE / RoHS
<b>Dimensions (WxDxH)</b>	36.5 x 26 x 35 cm
<b>Net Weight / Gross Weight</b>	6 kg / 8.6 kg
<b>Operating Temperature</b>	With extended temperature SSD/mSATA/ RAM/Adapter: from -20°C to 60°C with 0.7m/s air flow With standard system configurations: from 0°C to 50°C with 0.7m/s air flow
<b>Storage Temperature</b>	from -40°C to 85°C
<b>Humidity</b>	95% - 40°C (not condensing)

Performance relates to use of the product under optimal conditions.  
Right reserved to modify technical specifications.  
Registered trademarks are the property of their respective owners.  
FORM POS 960 is distributed by Olivetti S.p.A.  
(02/2018) - Code: 49698-00-w